

Item No.: DB701T(N) Transfer Silky Wall Covering Fabric

Application

Mural, Wall Covering

Technical Specifications

Base Material	100% Polyester	DIN 60001, ASTM D7641
Yarn	75D*300D	DIN EN 2060, ASTM D1907
Weave Method	Woven	---
Weight	195 ± 20gsm	ISO536
Thickness	550 ± 50 μ m	ISO534
Opacity	> 80%	ISO2471
Whiteness	125 ± 10	ISO11475
Color	L*: 91.0 ± 2.0; a*: 4.0 ± 2.0; b*: -10.0 ± 2.0	---
Gloss [60°]	6+/-2	Gloss [60°]
Shrinkage	≤ 3%	200° C, 45s
Flame Resistance	NO	---
Recommend Fixation Temperature	190-200°C, 45s	---
Yellowing Temperature	≥ 210°C	SUPRKC REX-C400, 30s

Size

Width	Max 3.20 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	100/300 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection.

It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

