

Item No.: AA602 Knitted Rubber Floor Mat

Application

Floor Mat

Technical Specifications

Base Material	100% Polyester	DIN 60001,ASTM D7641
Weave Method	Warp-Knitted	---
Weight	1500 ± 100gsm	ISO536
Thickness	2000 ± 300 μ m	ISO534
Opacity	> 99%	ISO2471
Whiteness	150 ± 10	ISO11475
Color	L*: 78.0 ± 2.0; a*: 7.0 ± 2.0; b*: -19.0 ± 2.0	---
Shrinkage	≤ 2%	200° C, 45s
Yellowing Δ E	≤ 2	200° C, 45s
Flame Resistance	NO	---
Recommend Fixation Temperature	190-200°C,45s	---
Yellowing Temperature	≥ 210°C	SUPRKC REX-C400,30s
Gloss[60°]	4 ± 2	GB/T 9754-2007

Size

Width	1.55 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	20 m/30 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection.

It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

