

## Item No.: DB101S Laminated Silky Wall Covering Fabric

### Application

Mural, Wall Covering

### Technical Specifications

Base Material	100% Polyester	DIN 60001, ASTM D7641
Yarn	75D*300D	DIN EN 2060, ASTM D1907
Weave Method	Woven	---
Total weight	230 ± 20gsm	ISO536
Thickness	470 ± 50 μ m	ISO534
Opacity	≥ 85%	GB/T 9754-2007
Whiteness	140 ± 10	ISO11475
Color	L*: 91.0 ± 2.0; a*: 6.0 ± 2.0; b*: -13.5 ± 2.0	GB/T 7974-2002
Gloss [60° ]	5 ± 2	GB/T 9754-2007
Shelf Time	1 year, unopened in original packaging	---
Flame Resistance	NO	---

### Size

Width	2.30 m/2.50 m/2.80 m/3.00 m/3.20 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	60 m	Standard	DIN EN ISO 3759, ASTM D751-2006

### Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

### Features



### Compatible Inks

