

Item No.: AD501 Mesh PVC Banner

Application

AD'&Promotion

Technical Specifications

Yarn	1000D*1000D,18*9	DIN EN ISO 2060,ASTM D1907
Weave Method	Warp-knitted	---
Weight	300g ± 20gsm	ISO536
Thickness	380 ± 40 μ m	ISO534
Whiteness	110 ± 10	ISO11475
Color	L*: 90.0 ± 2.0; a*: 3.0 ± 2.0; b*: -7.0 ± 2.0	---
Tensile Strength	MD: ≥ 1000N/5cm CD: ≥ 2500N/5cm	---
Tear Strength	MD: ≥ 100N/5cm CD: ≥ 70N/5cm	---
Flame Resistance	NO	---
Gloss[60°]	4 ± 2	---

Size

Width	2.6 m/3.2 m/5 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	50 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection.

It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

