

Item No.: AA601 Non Woven Rubber Floor Mat

Application

Floor Mat

Technical Specifications

Base Material	100% Polyester	DIN 60001,ASTM D7641
Yarn	6D	DIN EN 2060,ASTM D1907
Weave Method	Non-woven	---
Weight	1300 ± 150gsm	ISO536
Thickness	3200 ± 500 μ m	ISO534
Opacity	> 99%	ISO2471
Whiteness	135 ± 10	ISO11475
Color	L*:84.0 ± 2.0; a*: 7.5 ± 2.0; b*: -14.5 ± 2.0	---
Shrinkage	≤ 2%	200° C, 45s
Yellowing ΔE	≤ 2	200° C, 45s
Flame Resistance	NO	---
Recommend Fixation Temperature	190-200°C,45s	---
Yellowing Temperature	≥ 210°C	SUPRKC REX-C400,30s
Gloss[60°]	4 ± 2	GB/T 9754-2007

Size

Width	1.60 m/3.20 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	20 m/30 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks



Disclaimer:

The technical parameters of these products were tested in the laboratory environment, this is only serve as a reference. Before use, the user should determine the suitability of the product. Statements or recommendations contained in the technical information are not valid until the agreement is signed.