

Item No.: DB701T(N) Transfer Silky Wall Covering Fabric

Application

Mural, Wall Covering

Technical Specifications

Base Material	100% Polyester	DIN 60001, ASTM D7641
Yarn	75D*300D	DIN EN 2060, ASTM D1907
Weave Method	Woven	---
Weight	200 ± 20gsm	ISO536
Thickness	600 ± 60 μm	ISO534
Opacity	≥ 85%	GB/T 9754-2007
Whiteness	135 ± 10	ISO11475
Color	L*: 92.0 ± 2.0; a*: 5.5 ± 2.0; b*: -13.0 ± 2.0	GB/T 9794-2002
Gloss [60°]	6 ± 2	GB/T 9754-2007
Shelf time	1 year, unopened in original packaging	---
Shrinkage	≤ 2%	200° C, 45s
Yellowing ΔE	≤ 2	200° C, 45s
Flame Resistance	NO	---
Recommend Fixation Temperature	190-200°C, 45s	---
Yellowing Temperature	≥ 210°C	SUPRKC REX-C400, 30s

Size

Width	2.30 m/2.50 m/2.80 m/3.00 m/3.20 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	60 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

