

## Item No.: AM211L Outdoor PVC-FREE Frontlit Fabric

### Application

Outdoor AD&Promotion

### Technical Specifications

Material	100% Polyester	DIN 60001,ASTM D7641
Yarn	500D*500D	DIN EN ISO 2060,ASTM D1907
Weave Method	Woven	---
Weight	330 ± 20gsm	ISO536
Thickness	280 ± 30 μ m	ISO534
Opacity	> 97%	ISO2471
Whiteness	84 ± 10	ISO11475
Color	L*:95.0 ± 2.0; a*:-2.0 ± 2.0; b*:0 ± 2.0;	---
Gloss[60° ]	2 ± 1	---
Tensile Strength	Warp: ≥ 1600N/5cm; Weft: ≥ 1400N/5cm	---
Tear Strength	Warp: ≥ 250N/5cm; Weft: ≥ 250N/5cm	---
Flame Resistance	DIN 4102-1 B1,NFPA 701	DIN 4102-1 B1,NFPA 701
Outdoor Durability	>1 year	---

### Size

Width	Max 3.20m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	50 m	Standard	DIN EN ISO 3759, ASTM D751-2006

### Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

### Features



### Compatible Inks

