

Item No.: AM205 Recyclable PE Frontlit Banner

Application

Outdoor AD&Promotion

Technical Specifications

Material	100% Polyethylene	DIN 60001,ASTM D7641
Weave Method	Woven	---
Weight	160 ± 15gsm	ISO536
Thickness	180 ± 30 μ m	ISO534
Opacity	> 99%	ISO2471
Whiteness	70 ± 10	ISO11475
Color	L*:86.0 ± 2.0; a*:-1.0 ± 2.0; b*:-1.0 ± 2.0;	---
Gloss[60°]	12 ± 4	---
Tensile Strength	Warp: ≥ 800N/5cm; Weft: ≥ 700N/5cm	---
Tear Strength	Warp: ≥ 70N/5cm; Weft: ≥ 60N/5cm	---
Flame Resistance	NO	---
Outdoor Durability	>1 year	---

Size

Width	Max 3.20m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	100 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

