

Item No.: DB217FS-3S Solvent Self Adhesive Wall Covering Fabric

Application

Mural, Wall Covering Frame, Exhibition, Display systems

Technical Specifications

Substrate	220 ± 15g	GB/T 451.3-2002
Thickness	450 ± 50 μ m	ISO534
Material	100%Polyester	DIN 60001,ASTM D7641
Glue Weight	Grey Water- based Permanent Adhesive	---
Total Weight	50-60gsm	---
Liner	105gsm /DSPE	GB/T 451.2-2002
Total Weight	380 ± 30gsm	ISO536
Thickness	500 ± 50 μ m	ISO534
Opacity	≥ 95%	GB/T 9754-2007
Whiteness	115 ± 10	ISO11475
Color	L*:93.0 ± 2.0; a*: 5.0 ± 2.0; b*: -8.5 ± 2.0	GB/T 7974-2002
Peel Strength [lbf/in]15min [lbf/in]	> 2	FTM1-FINAT
Peel Strength [lbf/in] 24hrs [lbf/in]	> 4	FTM1-FINAT
Gloss [60°]	2 ± 1	GB/T 9754-2007
Shelf Time	1 year,unopened in original packaging	---
Flame Resistance	EN13501-1,DIN 4102-1-B1	EN13501-1,DIN 4102-1-B1

Size

Width	最大1.524 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	30 m/45 m/50 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

