

Item No.: DB208W-3S Aqueous Self Adhesive Wall Covering Fabric

Application

Mural, Wall Covering Frame, Exhibition, Display systems

Technical Specifications

Substrate	150 ± 15gsm	GB/T 451.3-2002
Thickness	170 ± 30 μ m	ISO534
Material	100% Polyester	DIN 60001, ASTM D7641
Glue Weight	Water Base Removable Grey Adhesive	---
Total Weight	40-45gsm	---
Liner	140gsm/DSPE	GB/T 451.2-2002
Total Weight	340 ± 20gsm	ISO536
Thickness	340 ± 40 μ m	ISO534
Opacity	≥ 95%	GB/T 9754-2007
Whiteness	130 ± 10	ISO11475
Color	L*:91.0 ± 2.0; a*: 4.5 ± 2.0; b*: -13.0 ± 2.0	GB/T 7974-2002
Peel Strength [lbf/in] 15min [lbf/in]	0.5-1.5	FTM1-FINAT
Peel Strength [lbf/in] 24hrs [lbf/in]	0.5-1.5	FTM1-FINAT
Gloss [60°]	2 ± 1	GB/T 9754-2007
Shelf Time	1 year, unopened in original packaging	---
Flame Resistance	NO	---

Size

Width	Max1.524 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	30 m/45 m/50 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks



Disclaimer:

The technical parameters of these products were tested in the laboratory environment, this is only serve as a reference. Before use, the user should determine the suitability of the product. Statements or recommendations contained in the technical information are not valid until the agreement is signed.