

Item No.: AD303M Blockout Matte PVC Banner

Application

Outdoor AD'&Promotion

Technical Specifications

Yarn	250D*250D,36*36C	DIN EN ISO 2060,ASTM D1907
Weave Method	Warp-knitted	---
Weight	440 ± 20gsm	ISO536
Thickness	380 ± 30 μ m	ISO534
Opacity	≥ 95	ISO2471
Whiteness	90 ± 10	ISO11475
Color	L*: 93.0 ± 2.0; a*:-1.0 ± 2.0; b*:-1.0 ± 2.0	---
Tensile Strength	MD: ≥ 1100N/5cm CD: ≥ 900N/5cm	---
Tear Strength	MD: ≥ 80N CD: ≥ 70N	---
Flame Resistance	NO	---
Gloss[60°]	5 ± 2	---

Size

Width	2.6 m/3.2 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	50 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

