

## Item No.: AD109G Frontlit Gloss PVC Banner

### Application

Outdoor AD'&Promotion

### Technical Specifications

|                  |  |                            |
|------------------|--|----------------------------|
| Yarn             | 840D*840D,18*18                                | DIN EN ISO 2060,ASTM D1907 |
| Weave Method     | Warp-knitted                                   | ---                        |
| Weight           | 440 ± 20gsm                                    | ISO536                     |
| Thickness        | 370 ± 30 μ m                                   | ISO534                     |
| Opacity          | ≥ 95   | ISO2471                    |
| Whiteness        | 130 ± 10                                       | ISO11475                   |
| Color            | L*: 91.0 ± 2.0; a*: 6.0 ± 2.0; b*: -12.0 ± 2.0 | ---                        |
| Tensile Strength | MD: ≥ 2000N/5cm CD: ≥ 2000N/5cm                | ---                        |
| Tear Strength    | MD: ≥ 250N CD: ≥ 200N                          | ---                        |
| Flame Resistance | NO   | ---                        |
| Gloss[60° ]      | 70 ± 10  | ---                        |

### Size

|        |                 |          |                                 |
|--------|-----------------|----------|---------------------------------|
| Width  | 2.6 m/3.2 m/5 m | Standard | DIN EN ISO 3759, ASTM D751-2006 |
| Length | 50 m            | Standard | DIN EN ISO 3759, ASTM D751-2006 |

### Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

### Features



### Compatible Inks

