

Item No.: AM212L Outdoor PVC-FREE Frontlit Fabric

Application

Outdoor AD&Promotion

Technical Specifications

| | | |
|--------------------|---|----------------------------|
| Material | 100% Polyester | DIN 60001,ASTM D7641 |
| Yarn | 1000D*1000D | DIN EN ISO 2060,ASTM D1907 |
| Weave Method | Woven | --- |
| Weight | 340 ± 20gsm | ISO536 |
| Thickness | 350 ± 30 μ m | ISO534 |
| Opacity | > 97% | ISO2471 |
| Whiteness | 84 ± 10 | ISO11475 |
| Color | L*:95.0 ± 2.0; a*:-2.0 ± 2.0; b*:0 ± 2.0; | --- |
| Gloss[60°] | 2 ± 1 | --- |
| Tensile Strength | Warp: ≥ 2100N/5cm; Weft: ≥ 2000N/5cm | --- |
| Tear Strength | Warp: ≥ 300N/5cm; Weft: ≥ 300N/5cm | --- |
| Flame Resistance | DIN 4102-1 B1,NFPA 701 | DIN 4102-1 B1,NFPA 701 |
| Outdoor Durability | >1 year | --- |

Size

| | | | |
|--------|-----------|----------|---------------------------------|
| Width | Max 3.20m | Standard | DIN EN ISO 3759, ASTM D751-2006 |
| Length | 50 m | Standard | DIN EN ISO 3759, ASTM D751-2006 |

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

